2022

can-am. **MAVERICK DS TURBO RR**

HIGHLIGHTS

піапсіапта	
DEFIANT	Trademark Can-Am DNA with next generation design Low seating position Ergo-Lok cockpit with four way adjustable seats
POWERFUL	 Industry leading 200 hp turbocharged and intercooled Rotax® ACE engine Advanced airflow dynamics QRS-X transmission
PRECISE	TTX suspension with industry leading travel Ultra efficient and lightweight chassis Sharpest handling features
PLATFORM FEATURES	• 64 in. (162.5 cm) wide • 102 in. (259.1 cm) wheelbase • 14 in. (35.6 cm) of ground clearance • High torque Dynamic Power Steering (DPS™) • 20 in. (50.8 cm) suspension travel • FOX† 2.5 PODIUM QS3 Piggyback shocks • 14 in. (35.6 cm) aluminum wheels • 30 in. (76.2 cm) Maxxis Carnivore† tires • 4.5 in. (11.4 cm) digital display with keypad • Rear tow hook
SPECIFIC TO DS TURBO RR PACKAGE	200 hp Turbo RR engine Belt monitoring system 850 W Magneto Horn, Buzzer, Evap system



ENGINE

Туре	149 kW (200 hp*), Rotax® ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and high- performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)

SUSPENSIONS

BRAKES

Front

Front Suspension	Double A-arm with sway bar / 20 in. (50.8 cm) travel
Front Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar / 20 in. (50.8 cm) travel
Rear Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment and bottom-out control
TIRES / WHEELS	
Front Tires	Maxxis Carnivore† 30 x 10 x 14 in. (76.2 x 25.4 x 35.6 cm)
Rear Tires	Maxxis Carnivore† 30 x 10 x 14 in. (76.2 x 25.4 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

Dual 262 mm disc brakes with hydraulic twin-piston calipers

Dual 248 mm disc brakes with hydraulic twin-piston calipers Rear

* 200 hp based US MY22 EPA certification or 195 hp based on European MY21 NRMM certification

DIMENSIONS	/ CAPACITIES

Estimated Dry Weight *	1,546 lb (701.3 kg)
Chassis / Cage	Dual-phase 980 steel
LxWxH	132 x 64 x 65.4 in. (335.3 x 162.5 x 166.1 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES

Gauge	4.5 in. (11.4 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO™ mode, seat
	belt and 4 x 4 indicator, front and rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS™ mode

Instrumentation	Lighter type DC Outlet in central console
Magneto	850 W
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Lighting	LED headlights and tail lights
Winch	N/A
Protection	Integrated front bumper Quarter-doors HMWPE full skid plate Rear tow hook

WARRANTY

Factory warranty	2-year BRP limited warranty



