

EVINRUDE® E-TEC®

135 H.O.



| | |
|------------------------------------|--|
| Engine Model | (a) E135HSL White (b) E135HGL Graphite (c) E135DHX White (d) E135HGX Graphite |
| Engine Type | V6 60° E-TEC D.I. |
| Bore x Stroke - in (mm) | 3.62 x 2.60 (92 x 66) |
| Displacement - cu in (cc) L | 158.2 (2592) 2.6L |
| Gear Ratio | (a)(b) 1.86:1 (c)(d) 1.85:1 |
| Full Throttle RPM Range | 5400-6000 RPM |
| Weight - lbs (kg) | (a)(b) 418 (190) (c)(d) 433 (196) |
| Starting | Electric |
| Controls | Mechanical (ICON EST Digital Accessory) |
| Fuel Induction | E-TEC Direct Injection with stratified low RPM combustion mode |
| Alternator Output* | 133 Amps Total / 50 Net Dedicated |
| Steering | Remote |
| Trim Method | FasTrak™ Power Trim and Tilt |
| Trim Range | -6° to 15° |
| Tilt Range | 75° |
| Shaft Length - in (mm) | (a)(b) 20 (508) (c)(d) 25 (635) |
| Lubrication | Multi-Point Targeted Oiling |
| Oil Tank Capacity - gal (L) | Accessory 1.8 (6.8) 3 (11.3) & 10 (37.85) Tank Available |
| Recommended Oil | Evinrude / Johnson XD-100 Oil |
| Recommended Fuel | 87 Octane |
| Counter Rotation | N/A |
| Warranty | 3-Year, Non-Declining |
| Emissions Compliance | EPA 2013 / CARB 3 STAR / European Union |

* Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

©2018 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

EVINRUDE®