

EVINRUDE® E-TEC® 30 HP



| | |
|------------------------------------|--|
| Engine Model | (a) E30DRS White (b) E30DRG Graphite (c) E30DRSL White (d) E30DRGL Graphite (e) E30GTSL Graphite (f) E30DTSL White (g) E30DGTL Graphite (h) E30DPSL White (i) E30DPGL Graphite |
| Engine Type | Inline 2-Cylinder E-TEC D.I. |
| Bore x Stroke - in (mm) | 2.992 x 2.5 (76 x 64) |
| Displacement - cu in (cc) L | 35.2 (577) |
| Gear Ratio | 2.15:1 |
| Full Throttle RPM Range | 5500-6000 RPM |
| Weight - lbs (kg) | (a)(b) 150 (68) (c)(d) 154 (70) (e) 166 (75) (f)(g) 187 (85) (h)(i) 181 (82) |
| Starting | (a)(b)(c)(d) Rope (Electric Accessory) (e)(f)(g)(h)(i) Electric and Rope |
| Controls | Mechanical |
| Fuel Induction | E-TEC Direct Injection with stratified low RPM combustion mode |
| Alternator Output* | 56 Amps Total / 15 Amps Net Dedicated |
| Steering | (a)(b)(c)(d)(e)(f)(g) Tiller (Remote Available) (h)(i) Remote (Tiller Available) |
| Trim Method | (a)(b)(c)(d)(e) Manual Tilt (f)(g)(h)(i) Power Trim and Tilt |
| Trim Range | -4° to 16° |
| Tilt Range | 65° |
| Shaft Length - in (mm) | (a)(b) 15 (381) (c)(d)(e)(f)(g)(h)(i) 20 (508) |
| Lubrication | Multi-Point Targeted Oiling |
| Oil Tank Capacity - gal | 1.7 (1.6) |
| Recommended Oil | Evinrude / Johnson XD-100 Oil |
| Recommended Fuel | 87 Octane |
| Warranty | 3-Year, Non-Declining |
| Emissions Compliance | EPA 2013 / CARB 3 STAR / European Union |

* Variable Voltage Computer Controlled 56 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 15 Amp.