

KUIAX ENGINE	1200 4-TEC
Engine details	Liquid-cooled, four-stroke D.O.H
	dry sump

Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	3
Displacement	1170.7 cc
Bore	91 mm
Stroke	60 mm
Maximum engine speed	7800 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	40 liters

DINTENICIONIC

COLOUR

UIIVIENSIUNS	
Vehicle overall length	3280 mm
Vehicle overall width	1290 mm
Vehicle overall height	1400 mm
Ski stance	1102 (-42) mm
Track nominal width	600 mm
Track nominal length	3968 mm
Track profile height	32 mm Ice Ripper (studded)

White/Orange

POWERTRAIN

Drive clutch type	eDrive II
Driven clutch type	QRS SS
Small sprocket number of teeth	1st gear = 3.86:1
Large sprocket number of teeth	2nd gear = 2.3:1
Drive sprocket	8
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

Front suspension	A-LFS
Front shock	HPG 36
Rear suspension	PPS-6900-F
Center shock	HPG 36
Rear shock	2 x HPG 36

FEATURES

Frame	L-XU
Skis	Blade XC
Seating	Modular, 1+1
Handlebar	U-type steel with hooks, mountain strap
Riser block height	130 mm
Starter	Electric
Reverse	Mechanical (2F-N-R)

Heated throttle lever	Standard
Heated grips	Standard
Gauge	Multifunction
Mirrors	Standard
Windshield	High (510 mm), one piece
Hitch	Standard
Visor Plug front / rear	-
12V power outlet	Front



