



ROTAX° ENGINE	900 ACE
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	3

Displacement 899.0 cc

Bore 74 mm

Stroke 69.7 mm

Maximum engine speed 7250 RPM

Carburation EFI

Recommended fuel type Unleaded

Minimum octane 95

40 liters

DIMENSIONS

COLOUR

DIIVIEIVƏIDIVƏ	
Vehicle overall length	3280 mm
Vehicle overall width	1180 mm
Vehicle overall height	1430 mm
Ski stance	996 (+/- 21) mm
Track nominal width	600 mm
Track nominal length	3968 mm
Track profile height	32 mm

White/Orange

POWERTRAIN

Fuel tank

Drive clutch type	eDrive II
Driven clutch type	QRS SS
Small sprocket number of teeth	1st gear = 3.86:1
Large sprocket number of teeth	2nd gear = 2.3:1
Drive sprocket	7
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

Front suspension	A-LFS+ with bended lower A-Arms
Front shock	HPG 36
Rear suspension	PPS-6900-A
Center shock	HPG 25
Rear shock	HPG 36

FEATURES

Frame	L-XU
Skis	Blade XC
Seating	Modular, 1-up heated
Handlebar	U-type steel with hooks, mountain strap
Riser block height	Adjustable 130-205 mm
Starter	Electric
Reverse	Mechanical (2F-N-R)

Heated throttle lever	Standard
Heated grips	Standard
Gauge	Analog with display
Mirrors	Standard
Windshield	High (510 mm), one piece
Hitch	Standard
Visor Plug front / rear	Front
12V power outlet	Front



