

69 YETI ARMY

2020



ROTAX® ENGINE

600 E-TEC

Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	594.4 cc
Bore	72 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	40 liters
Oil tank capacity (2-stroke)	2,9 liters

POWERTRAIN

Drive clutch type	TRA 3
Driven clutch type	QRS SS
Small sprocket number of teeth	1st gear = 3.23:1 ratio
Large sprocket number of teeth	2nd gear = 1.98:1 ratio
Drive sprocket	8
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

FEATURES

Frame	L-XU
Skis	Blade XC + ski liners
Seating	Modular, 1+1
Handlebar	U-type steel with hooks, mountain strap
Riser block height	Adjustable 130-205 mm
Starter	Manual, Electric
Reverse	Mechanical (2F-N-R)

COLOUR



DIMENSIONS

Vehicle overall length	3390 mm
Vehicle overall width	1120 mm
Vehicle overall height	1420 mm
Ski stance	900 mm
Track nominal width	600 mm
Track nominal length	3968 mm
Track profile height	32 mm Ice Ripper (studded)

SUSPENSION

Front suspension	LTS
Front shock	MC
Rear suspension	PPS-6900-A
Center shock	HPG 25
Rear shock	HPG 36

Heated throttle lever	Standard
Heated grips	Standard
Gauge	Analog with display
Mirrors	Standard
Windshield	High (510 mm), one piece
Hitch	Standard
Visor Plug front / rear	Front
12V power outlet	Front