

ROTAX [®] ENGINE	600 EFI	600 ACE
Engine details	Liquid-cooled, two-stroke	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	2
Displacement	599.4 cc	600 cc
Bore	72.3 mm	74 mm
Stroke	73 mm	69.7 mm
Maximum engine speed	7500 RPM	7250 RPM
Carburation	EFI	EFI
Recommended fuel type	Unleaded	Unleaded
Minimum octane	95	95
Fuel tank	42 liters	42 liters
Oil tank capacity (2-stroke)	3.4 liters	

COLOUR

Viper Red/Black

2021

DIMENSIONS

3230 mm
1200 mm
1490 mm
996 mm
500 mm
3923 mm
38 mm (600 EFI) 44 mm (600 ACE)

POWERTRAIN

eDrive II (600 ACE) QRS	
Hydraulic brake with braided steel brake line, plastic master cylinder	

SUSPENSION

LFS
MC
EasyRide (600 EFI) EasyRide with adjustment (600 ACE)
HPG 36
HPG 36

FEATURES

Radien-X	
Blade DS+	
Modular, 1-up	
U-type steel with hooks, low grab handle (grab handle only in 600 ACE)	
140 mm	
Electric (600 ACE) Electric and manual (600 EFI)	
RER (600 EFI) Electromechanical (ACE)	

Heated throttle lever	Standard	
Heated grips	Standard	
Gauge	4.5-in. digital display	
Mirrors		
Windshield	Extra high with side deflectors	
Hitch	Standard (only on 600 ACE)	
Visor Plug front / rear	Front (only on 600 ACE)	
12V power outlet	Front (only on 600 ACE)	

* Vehicle overall length without snowflap.

©2020 Bombardier Recreational Products Inc., (BRP). All rights reserved. [™],^{*} and the BRP logo are trademarks of BRP or its affiliates. [†]All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

