

ROTAX® ENGINE	600R E-TEC	850 E-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2	2
Displacement	599.4 cc	849 cc
Bore	72,3 mm	82 mm
Stroke	73 mm	80.4 mm
Maximum engine speed	8100 RPM	7900 RPM
Carburation	Electronic Direct Injection	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Unleaded	Unleaded
Minimum octane	95	95
Fuel tank	37 liters	37 liters
Oil tank capacity (2-stroke)	3.4 liters	3.4 liters

3300 mm
1120 mm
1300 mm
921 mm
400 mm
3912 mm
64 mm PowderMax Light FlexEdge

POWERTRAIN

Drive clutch type	pDrive with clickers	
Driven clutch type	QRS	
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder	

SUSPENSION

Front suspension	LFS	
Front shock	HPG 36	
Rear suspension	PPS ² -DS+ -3900	
Center shock	HPG 36	
Rear shock	HPG 36	

FEATURES

Frame	Radien	
Skis	Blade DS+	
Seating	Sport, 1-up	
Handlebar	U-type aluminium with hooks, low grab handle	
Riser block height	140 mm	
Starter	Electric and manual	
Reverse	RER	

Heated throttle lever	Standard	
Heated grips	Standard	
Gauge	7.2-in. wide digital display	
Mirrors		
Windshield	Medium with side deflectors	
Hitch		
Visor Plug front / rear	Front	
12V power outlet	Yes, in front compartment	



^{*} Vehicle overall length without snowflap.