

ROTAX® ENGINE	600 ACE
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters

Viper Red/Black
3060 mm
1280 mm
1470 mm
1080 mm
381 mm
3487 mm
34 mm Cobra

POWERTRAIN

Drive clutch type	eDrive II
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

Front suspension	LFS
Front shock	HPG 36
Rear suspension	PPS ² -3500
Center shock	HPG 36
Rear shock	HPG 36

FEATURES

,	
Frame	Radien-X
Skis	Blade DS+
Seating	2-up
Handlebar	Steel with hooks
Riser block height	120 mm
Starter	Electric
Reverse	Mechanical
Heated throttle lever	Standard

Heated grips	Standard
Gauge	4.5-in. digital display
Mirrors	
Windshield	Extra high with side deflectors
Hitch	
Visor Plug front / rear	Front
12V power outlet	Yes, in front compartment



 $^{^{\}ast}$ Vehicle overall length without snowflap.