

ROTAX® ENGINE	900 ACE
Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	3
Displacement	899.0 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters

Viper Red/Black
3250 mm
1200 mm
1300 mm
996 mm
406 mm
3705 mm
39 mm DSG

## **POWERTRAIN**

Drive clutch type	pDrive
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

## **SUSPENSION**

Front suspension	LFS
Front shock	KYB 36
Rear suspension	PPS <sup>2</sup> -3700
Center shock	KYB 36
Rear shock	KYB 46

## **FEATURES**

Frame	Radien-X
Skis	Blade DS+
Seating	Sport, 1-up
Handlebar	Straight steel with hooks
Riser block height	120 mm
Starter	Electric
Reverse	Mechanical
Heated throttle lever	Standard

Heated grips	Standard
Gauge	7.2-in. wide digital display
Mirrors	
Windshield	Medium with side deflectors
Hitch	Standard
Visor Plug front / rear	Front
12V power outlet	Yes, in front compartment



 $<sup>^{\</sup>ast}$  Vehicle overall length without snowflap.