

ROTAX [®] ENGINE	900 ACE Liquid-cooled, four-stroke D.O.H.C.		
Engine details			
Cylinders	3		
Displacement	899.0 cc		
Bore	74 mm		
Stroke	69.7 mm		
Maximum engine speed	7250 RPM		
Carburation	EFI		
Recommended fuel type	Unleaded		
Minimum octane	95		
Fuel tank	42 liters		

COLOUR

White/Orange/Black

DIMENSIONS

Vehicle overall length*	3240 mm	
Vehicle overall width	1200 mm	
Vehicle overall height	1500 mm	
Ski stance	996 mm	
Track nominal width	600 mm	
Track nominal length	ength 3923 mm	
Track profile height	38 mm	

POWERTRAIN

Gearbox	2F/N/R with push-button reverse		
Drive clutch type	pDrive with slider shoes		
Driven clutch type	QRS		
Brake system Hydraulic brake with braided steel bral plastic master cylinder			

SUSPENSION

Front suspension	LFS with bended lower A-Arms		
Front shock	HPG 36		
Rear suspension	EasyRide with adjustment		
Center shock	HPG 36		
Rear shock	HPG 36		

FEATURES

Frame	Radien-X	Heated grips	Standard
Skis	Blade DS+	Gauge	4.5-in. digital display
Seating	Modular, 1-up heated	Mirrors	Standard
Handlebar	U-type steel with hooks, low grab handle	Windshield	Extra high with side deflectors
		Hitch	Standard
Riser block height	145 mm	Visor Plug front / rear	Front
Starter	Electric	12V power outlet	Front
Reverse	Electromechanical	Air radiator with fan	Yes
Heated throttle lever	Standard	LinQ attachment	Multi-LinQ plate

* Vehicle overall length without snowflap.

©2020 Bombardier Recreational Products Inc., (BRP). All rights reserved. [™],^{*} and the BRP logo are trademarks of BRP or its affiliates. [†]All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

