

ROTAX® ENGINE

900 ACE Turbo

Engine details	Liquid-cooled, four-stroke D.O.H.C., turbocharged		
Cylinders	3		
Displacement	899.0 cc		
Bore	74 mm		
Stroke	69.7 mm		
Maximum engine speed	7750 RPM		
Carburation	EFI		
Recommended fuel type	Unleaded		
Minimum octane	95		
Fuel tank	42 liters		

COLOUR

Noble Bronze/Black

DIMENSIONS

Vehicle overall length*	3240 mm	
Vehicle overall width	1280 mm	
Vehicle overall height	1470 mm	
Ski stance	1080 mm	
Track nominal width	600 mm	
Track nominal length	3923 mm	
Track profile height	38 mm	

POWERTRAIN

Gearbox	2F/N/R with push-button reverse		
Drive clutch type	pDrive		
Driven clutch type	QRS		
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder		

SUSPENSION

Front suspension	LFS	
Front shock	KYB 36 R	
Rear suspension	EasyRide with adjustment	
Center shock	KYB 46 Kashima	
Rear shock	KYB 46 Kashima	

FEATURES

Frame	Radien-X	Heated grips	Standard
Skis	Blade DS+	Gauge	7.2-in. wide digital display
Seating	Luxury Modular 1+1 with heating	Mirrors	Standard
Handlebar	U-type steel with hooks, low grab handle	Windshield	Extra high with side deflectors
		Hitch	Standard
Riser block height	Adjustable 125-165 mm	Visor Plug front / rear	Front/Rear
Starter	Electric	12V power outlet	Front
Reverse	Electromechanical	Air radiator with fan	Yes
Heated throttle lever	Standard	LinQ attachment	Multi-LinQ plate

* Vehicle overall length without snowflap.

©2020 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™,* and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

