

2020 RENEGADE[®] X[®] xc 1000 T

HIGHLIGHTS

- Rotax[®] V-twin engine
- Intelligent Throttle Control (iTCTM) with riding modes
- Anti-Lock Brake System (ABS)
- Front and rear FOX[†] PODIUM[†] 1.5 RC2 shocks
- Arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS[™])
- 12-in. cast-aluminum beadlock wheels
- 25-in. ITP Holeshoot[†] ATR tires
- Front & central skid plate
- Aluminum taper-profile handlebar with wind deflectors and square pad
- Torsional Trailing arm Independent (TTI) rear suspension
- Multifunction digital gauge
- X-package coloration, graphics and seat cover



Black & Can-Am Red

ENGINES

1000

Type	82 hp, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTCTM) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Brake Traction Control (BTC)
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed category	More than 60 km/h

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 23.3 cm travel
Front Shocks	FOX [†] PODIUM [†] 1.5 RC2
Rear Suspension	Torsional Trailing arm Independent (TTI) 25.1 cm travel
Rear Shocks	FOX [†] PODIUM [†] 1.5 RC2

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brakes with hydraulic twin-piston calipers
ABS	Standard

FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	240 W from 4 fender mounted projector beam headlamps (60 W) with tail light / brake light
T-category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn	Seat	Standard
		Anti-theft System	Digitally Encoded Security System (D.E.S.S.)
		Protection	Front bumper, aluminum taper-profile handlebar with wind deflectors and square pad, front & central skid plate, mudguards

WARRANTY

Factory	2 years
---------	---------

TIRES / WHEELS

Front Tires	ITP Holeshoot ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	ITP Holeshoot ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum beadlocks

DIMENSIONS / CAPACITIES

L x W x H	218.4 x 122 x 124 cm
Wheelbase	129.5 cm
Ground Clearance	26.7 cm
Seat Height	87.7 cm
Dry Weight*	323 kg
Rack Capacity	Rear: 16 kg
Storage Capacity	N/A
Towing Capacity	660 kg trailer with brakes and 335 kg trailer without brakes
Fuel Capacity	20.5 L