Can-am. COMMANDER XT-P 1000R

HIGHLIGHTS

DARING	 Sturdy engine and transmission Enhanced comfort and meaningful functionalities Can-Am design
PRECISE	 Easy handling and capabilities Suspension designed for performance Ultra-resistant chassis
CAPABLE	Work or ride with confidence Meaningful and versatile functionality Easy handling and capabilities
PLATFORM FEATURES	90.6 in. wheelbase 13.5 in. ground clearance 14 in. suspension travel 2,000 lb towing capacity Dynamic Power Steering (DPS™) SPORT/ECO™ modes D.E.S.S. key with Start/Stop button Premium half doors Mudguards Rear differential with Turf mode
SPECIFIC TO XT-P PACKAGE	64 in. wide with arched double A-arm Smart-Lok* front differential FOX' 2.5 PODIUM QS3 Piggyback shocks 30 in. XPS Hammer Force tires 15 in. cast-aluminum beadlock wheels XT front bumper 4,500 lb (2,014 kg) winch Full roof and panoramic mirror 7.6 in. digital display with keypad LED headlight and Can-Am LED signature Painted color

ENGINE	1000R
--------	-------

Type	100 hp, Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L/H/N/R/P
Drive Train	Selectable Turf Mode/2WD/4WD TRAIL/4WD TRAIL ACTIV with exclusive Smart-Lok technology
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar/14 in. (35.6 cm) travel
Front Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment
Rear Suspension	Arched TTA with sway bar/14 in. (35.6 cm) travel
Rear Shocks	FOX [†] 2.5 PODIUM Piggyback with QS3 [†] compression adjustment

TIRES & WHEELS

Front Tires	XPS Hammer Force 30 x 10 x 15 in. (76.2 x 25.4 x 38.1 cm)
Rear Tires	XPS Hammer Force 30 x 10 x 15 in. (76.2 x 25.4 x 38.1 cm)
Wheels	15 in. (38.1 cm) cast-aluminum beadlock

BRAKES

DITTUICE	
Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers



DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,725 lb (782.4 kg)
Chassis/Cage	Profiled cage ROPS approved
LxWxH	130 x 64 x 75.3 in (330.2 x 162.6 x 191.2 cm)
Wheelbase	90.6 in. (230.1 cm)
Ground Clearance	13.5 in (34.3 cm)
Cargo Box Dimensions	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,030 lb (467.2 kg)
Storage Capacity	Total: 7.3 gal (27.6 L) Glove box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and cup holders: 0.8 gal (3.1 L) Side cargo box storage (passenger side): 1.6 gal (5.9 L) Dual-side panel storage: 0.8 gal (3.0 L)
Fuel Capacity	10 gal (38 L)

FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO TM modes, seat belt and 4 x 4 indicator, front and rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature
Instrumentation	Lighter-type DC outlet in console (10 A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Magneto	650 W
Lighting	LED headlights and taillights with unique Can-Am LED signature
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Steering Wheel	Adjustable tilt steering
Protection	Premium half doors Full skid plate Mudguards XT front bumper Full roof
Hitch Type	2 in. hitch receiver

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months

