

Can-am. OUTLANDER 6X6 XU+ 450 T

450

ENGINE

ENGINE	450
Туре	38HP, Rotax 427 cc single cylinder, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 4WD / 6WD with Visco-Lok QE auto- locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed Category	Up to 60 km/h
SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 8.8 in. (22 cm) travel
Rear Shocks	Oil
TIRES / WHEELS	
Front Tires	Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum
BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper
DIMENSIONS / CAPACITIES	
Estimated Dry Weight *	443 Kg
LxWxH	279 x 118,8 x124 cm
Wheelbase	208 cm
Ground Clearance	26,7 cm
Seat Height	85,8 cm
Rack Capacity	Front: 54 kg / Rear: 159kg
Storage Capacity	Rear: 70 L
Towing Capacity	907 Kg trailer with brakes 465 Kg trailer without brakes
Fuel Capacity	20.5 L



Gauge	4.5-in. digital display: Speedometer, tachometer, odometer, trip & hour meters, gear position, 4 x 4 indicato
	temperature, engine lights, electronic fuel gauge & clock
Instrumentation	Lighter type DC Outlet in console, standard connector in the back (15-A)
Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
Lighting	70 W from dual 35-W front light and dual 55-W reflectors with tail light / brake light
Winch	3,500-lb (1,588 kg) winch
T-Category features	Towing hitch with trailer plug, directionnal indicators, position lamps, mirrors, horn
Seat	Reinforced seat skin
Protection	Heavy-Duty front bumper, Central skid plate, heated grips
WARRANTY	
Factory warranty	2-years BRP limited warranty

