

can-am

OUTLANDER MAX 6X6 XU+ 650 T

2021



Tundra Green

| ENGINE | 650 |
|----------------------|--|
| Type | 59HP, Rotax 649.6 cc V-twin, liquid cooled |
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) |
| Transmission | CVT, P / R / N / H / Extra Low L, standard engine braking |
| Drive Train | Selectable 4WD / 6WD with Visco-Lok QE auto-locking front differential |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) |
| Speed Category | Up to 60 km/h |

| SUSPENSIONS | |
|------------------|--|
| Front Suspension | Arched double A-arm with front sway bar 9.2 in. (23.3cm) travel |
| Front Shocks | Oil |
| Rear Suspension | Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25,1 cm) travel |
| Rear Shocks | Oil |

| TIRES / WHEELS | |
|----------------|--|
| Front Tires | Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm) |
| Rear Tires | Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm) |
| Wheels | 12-in. cast-aluminum |

| BRAKES | |
|--------|--|
| Front | Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers |
| Rear | Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers |

| DIMENSIONS / CAPACITIES | |
|-------------------------|---|
| Estimated Dry Weight * | 499 kg |
| L x W x H | 317 x 123 x 140 cm |
| Wheelbase | 228,5cm |
| Ground Clearance | 27,9 cm |
| Seat Height | 87,7 cm |
| Rack Capacity | Front: 45 kg / Rear: 318 kg |
| Storage Capacity | Dual-level cargo box with sidewalls and tailgate Rear: 18,5 gal (70 L) |
| Towing Capacity | 907 Kg trailer with brakes 674 Kg trailer without brakes |
| Fuel Capacity | 20,5 L |

| FEATURES | |
|---------------------|--|
| Gauge | 4.5-in. digital display: Speedometer, tachometer, odometer, trip & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock |
| Instrumentation | Lighter type DC Outlet in console, standard connector in the back (15-A) |
| Anti-theft System | Digitally Encoded Security System (D.E.S.S.™) |
| Lighting | 230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light |
| Winch | 3,500-lb (1,588 kg) winch |
| T-Category features | Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn |
| Seat | Reinforced seat skin Convertible Rack System (CRS) |
| Protection | Heavy-Duty front bumper, Central skid plate, heated grips |

| WARRANTY | |
|------------------|------------------------------|
| Factory warranty | 2-years BRP limited warranty |

©2020 Bombardier Recreational Products Inc (BRP). All rights reserved.™, * and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. †All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

