Can-am. OUTLANDER XU+ 570/650 T

HIGHLIGHTS

- Rotax[®] V-twin engine
- Arched double A-arm front suspension with front sway bar
 Intelligent Throttle Control (iTC™) with riding modes
- Continuously Variable Transmission (CVT) with Extra Low L gear • Tri-Mode Dynamic Power Steering (DPS™)
- 3,500-lb (1,588 kg) winch
- 12-in. cast-aluminum wheels
 26-in. 6-ply Carlisle† ACT HD radial tires
- Reinforced seat skin
- Relocated air intakes
- Increased ground clearance
- Digitally Encoded Security System (D.E.S.S.™)
- High strength multi-functions racks with LinQ[™] quick-attach accessory
- 21.4 L water-resistant rear compartment
- Heated hand grips
- Mudguards

· Heavy duty front bumper



ENGINES	570	650
Туре	48HP, Rotax V-twin, liquid cooled	59HP, Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	CVT, P / R / N / H / Extra low L, standard engine braking	
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	
Speed Category	Up to 60 km/h	

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3cm) travel	
Front Shocks	Oil	
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25,1 cm) travel	
Rear Shocks	Oil	

TIRES / WHEELS

Front Tires	Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

RBAKES

hydraulic twin-piston calip	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
8	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

Estimated Dry Weight * 749 (341 kg) LxWxH 86 x 48 x 49.5 in. (218.4 x 121.9 x 126 cm) Wheelbase 51 in. (129.5 cm) Ground Clearance 12 in. (30.5 cm) Seat Height 34.5 in. (87.7 cm) **Rack Capacity** Front: 100 lb (45 kg) / Rear: 200 lb (90 kg) Storage Capacity Rear: 5.7 gal (21.4 L) **Towing Capacity** 750 Kg trailer with brakes and 335 kg trailer without brakes **Fuel Capacity** 5.4 gal (20.5 L) FEATURES

DIMENSIONS / CAPACITIES

Gauge	4.5-in. digital display:
	Speedometer, tachometer, odometer,
	trip & hour meters, gear position,
	4 x 4 indicator, temperature, engine lights,
	electronic fuel gauge & clock
Instrumentation	Lighter type DC Outlet in console, standard
	connector in the back (15-A)
Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
Lighting	230 W from twin 60-W projectors and dual
	55-W reflectors with tail light / brake light
Winch	3,500-lb (1,588 kg) winch
T-Category features	Towing hitch with trailer plug, directional
0 ,	indicators, position lamps, mirrors, horn
Seat	Reinforced seat skin
Protection	Heavy-duty front bumper
	Heated grips
	Mudguards
	-

WARRANTY

Factory warranty

2-years BRP limited warranty

©2020 Bombardier Recreational Products Inc (BRP). All rights reserved. "¹, * and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. *Visco-Lok is a trademark of GKN Viscodrive GmbH. *All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right, at any time, to discontinue or change specifications, prices, your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs dont mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never earry passengers on any ATV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

