



HIGHLIGHTS

- Rotax® engine options
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- 26-in. Carlisle ACT HD 6-ply tires
- 12-in, steel wheels
- Double A-arm front suspension
- Torsional Trailing arm Independent (TTI) rear suspension
- Visco-Lok QE auto-locking front differential
- 1,300-lb (590 kg) towing capacity
- Heavy-duty front bumper
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- RF Digitally Encoded Security System (D.E.S.S.)
- 500-W magneto
- Multifunction digital gauge
- Steel racks with LinQ quick-attach accessory system and a combined 360 pounds (163.3 kg) capacity
- 2.9-gal (10.9 L) water-resistant rear compartment



Type 38HP, Rotax 427 cc single cylinder, liquid cool liquid cooled Fuel Delivery System Intelligent Throttle Control (iTC™) w	,	
Fuel Delivery System Intelligent Throttle Control (iTCTM) w		
Electronic Fuel Injection (EFI)	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission CVT, P / R / N / H / L, standard engine b	CVT, P / R / N / H / L, standard engine braking	
Drive Train Selectable 2WD / 4WD with Visco-Lok QE auto-locking front difference.	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential	
Power Steering Tri-Mode Dynamic Power Steering (D	Tri-Mode Dynamic Power Steering (DPS)	
SUSPENSIONS		
Front Suspension Double A-arm 9 in. (22.9 cm) travel		
Front Shocks Oil	Oil	
Rear Suspension Torsional Trailing arm Independent (* 8.8 in. (22.4 cm) travel	Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel	
Rear Shocks Oil	Oil	
TIRES / WHEELS		
Front Tires Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)		
Rear Tires Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)	Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)	
Wheels 12-in. Steel	12-in. Steel	
BRAKES		
Front Dual 214 mm ventilated disc brakes ventilated ventilated disc brakes ventilated ventilated ventilated ventilated ventilated ventilated ventilated ventilated ventilated ventilate	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers	
Rear Single 214 mm ventilated disc brake hydraulic twin-piston caliper	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper	

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	678 lb (308 kg)	704 lb (319 kg)	
LxWxH	83 x 46 x 49 in. (211 x 116.8 x 124 cm)		
Wheelbase	51 in. (129.5 cm)		
Ground Clearance	11.5 in. (29.2 cm)		
Seat Height	33.8 in. (85.8 cm)		
Rack Capacity	Front: 120 lb (54.4 kg) /		
	Rear: 240	lb (109 kg)	
Storage Capacity	Rear: 2.9 gal (10.9 L)		
Towing Capacity	1,300 lb (590 kg)		
Fuel Capacity	5.4 gal (20.5 L)		

FEATURES

Gauge	4.5-in. digital display:
•	Speedometer, tachometer, odometer,
	trip & hour meters, gear position, 4 x 4 indicator,
	temperature, engine lights,
	electronic fuel gauge & clock
Instrumentation	Lighter type DC Outlet in console, standard
	connector in the back (15-A)
Anti-theft System	RF Digitally Encoded Security System
•	(D.E.S.S.™)
Lighting	70 W from dual 35-W front light / brake light
Winch	Prewired for available winch
Seat	Reinforced seat skin
Protection	Heavy-duty front bumper

WARRANTY

Factory warranty	2-years BRP limited warranty
raciory warranty	2-years one illilited warranty



