



HIGHLIGHTS	
TOUGH	Heavy-duty Rotax® engine     Smooth, durable and responsive transmission     True Can-Am DNA with a strong identity
CAPABLE	Work or ride with confidence     Meaningful and versatile functionality     Easy handling and capabilities
CLEVER	Advanced comfort and intuitive cockpit with optimized visibility     Multifunction cargo box with sturdy tailgate and smart storage     1-year maintenance free and easy access to key maintenance     components
PLATFORM FEATURES	• 62 in. wide • 83 in. wheelbase • Dynamic Power Steering (DPS) • ECO™ / ECO™ Off / Work modes • 2,500 lb towing capacity • Multi function cargo box • 27 in. Maxxis† Coronado • Rear differential with Turf mode • 7.6 in. digital display • 11 in. of ground clearance
SPECIFIC TO	Visco-Lok QE front differential     14 in cast-aluminum wheels



- VERSA-PRO bench seat with passenger seats flipping up
- · HMWPE full skid plate
- 4,500-lb (2,014 kg) winch
- Brake holding mechanism
   Horn, flashers and position lamps, lateral mirrors, license plate support, hook on front metal bumper

ENGINES	HD8
Туре	50 hp / 50 lb-ft , Rotax® 799.9 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ Transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection  Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Visco-Lok† QE auto- locking front differential
Driving Assistance	Electronic Hill Descent Control ECO™ / ECO™ Off / Work modes Brake holding mechanism
Power Steering	Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Double A-arm / 10 in. (25.4 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	TTA with external sway bar / 10 in. (25.4 cm) travel
Rear Shocks	Twin tube gas charged shocks
TIRES / WHEELS	
Front Tires	Maxxis Coronado 2.0† 27 x 9 x 14 in. (68.6 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Coronado 2.0† 27 x 11 x 14 in. (68.6 x 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum
BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic single-piston calipers
	Brake holding mechanism





## **DIMENSIONS / CAPACITIES**

Cage	Profiled cage. ROPS approved
Estimated Dry Weight*	1,580.7 lb (717 kg)
LxWxH	121 x 62 x 76 in. (307.1 x 157.5 x 193 cm)
Wheelbase	83 in. (211.5 cm)
Ground Clearance	11 in. (28 cm)
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg)
Power tilt bed	N/A
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 14.3 gal (54.2 L) Under dash: 6 gal (22.8 L) Waterproof and removable box under passenger seat: 5.6 gal (21 L) Dash: 1.8 gal (6.9 L) Armrests and cup holders: 0.9 gal (3.5 L)
Towing Capacity	2,500 lb (1134 kg)
Payload Capacity	1,500 lb (680 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	3

Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, ECO / ECO Off / Work modes, seat belt and 4 x4 indicator, front and rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature
Battery	12-V (30 amp/h)
Magneto	650-W
Instrumentation	Lighter type DC outlet in console (20-A)
Lighting	140 W lighting output from four 35-W reflectors ensuring a wide visiblity and Premium LED tail lights
Winch	4,500-lb (2,041 kg) winch with roller fairlead
Seat	VERSA-PRO bench seat with passenger seats flipping up, underside hooks and contoured bench to improve entrance/exit of the cab
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper HMWPE full skid plate
Hitch Type	2-in hitch receiver with rear hitch and tow ball
WARRANTY	
Factory warranty	2-years BRP limited warranty



