



HIGHLIGHTS

- Rotax® V-Twin engine
- Arched double A-arm front suspension with front sway bar
 Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
 Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Torsional Trailing arm Independent (TTI) rear suspension
 Visco-Lok† QE auto-locking front differential
- 14-in. (35.6 cm) cast-aluminum wheels
- Heavy-duty front bumper230-W lighting from headlights
- 650-W magneto
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- 5.7-gal (21.4 L) water-resistant rear compartment RF Digitally Encoded Security System (D.E.S.S.™)
- · Multifunction digital gauge



ENGINE	
Type	68 k W (91 hp), Rotax® 976 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	

SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar
	9.2 in. (23.3 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel
Rear Shocks	Oil

TIRES / WHEELS	
Front Tires	ITP† Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Rear Tires	ITP† Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. (35.6 cm) cast-aluminum
BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	749 lb (341kg)
LxWxH	86 x 48 x 49.5 in. (218.4 x 121.9 x 126 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	11 in. (27.9 cm)
Seat Height	34.5 in. (87.7 cm)
Rack Capacity	Front: 100 lb (45 kg) /
	Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,650 lb (750 kg)
Fuel Capacity	5.4 gal (20.5 L)

EEATLIDES

Gauge	4.5 in. digital display:
	Speedometer, tachometer, odometer,
	trip & hour meters, gear position,
	4 x 4 indicator, temperature, engine lights,
	electronic fuel gauge & clock
Instrumentation	Lighter type DC Outlet in console, standard
	connector in the back (15-A)
Anti-theft System	RF Digitally Encoded Security System
	(D.E.S.S.™)
Lighting	230 W from twin 60-W projectors and dual
	55-W reflectors with tail light / brake light
Winch	Prewired for available winch
Seat	Standard
Protection	Heavy-Duty front bumper,
	Mudguards

WARRANTY

Factory warranty 2-year BRP limited warranty



twin-piston caliper

