

can-am. **OUTLANDER MAX 6X6 XU+ 1000 T**

HIGHLIGHTS

- Rotax® V-Twin engine
- Arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with extra low L-gear
- 3,500-lb (1,588 kg) winch
- Speed limiter
- 700-lb (318 kg) capacity Dual-Level cargo box with modular accessories
- Heavy-Duty front bumper
- 26 in. (66 cm) Carlisle ACT HD 6-ply tires
- 12 in. (30.5 cm) cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS™)
- Heated grips & throttle
- Double Torsional Trailing arm Independent (TTI2) rear suspension
- Quick release rear sway bar
- · Relocated air intakes
- RF Digitally Encoded Security System (D.E.S.S.™)
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- Convertible Rack System (CRS) with LinQ™ system
- Dynamic passenger comfort ergonomicsMultiposition passenger handgrips
- Raised floorboards



M		IГ	ч	Е
w	a	ш	u	

Туре	60 kW (80 hp), Rotax® 976 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 4WD / 6WD with Visco-Lok† QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed Category	Up to 60 km/h

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	Oil
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25.1 cm) travel
Rear Shocks	Oil

TIRES / WHEELS

Front Tires	Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12 in. (30.5 cm) cast-aluminum

BRAKES

Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	597 kg
LxWxH	317 x 123 x 140 cm
Wheelbase	228.5 cm
Ground Clearance	27.9 cm
Seat Height	87.7 cm
Rack Capacity	Front: 45 kg / Rear: 318 kg
Storage Capacity	Dual-level cargo box with sidewalls and tailgate Rear: 18.5 gal (70 L)
Towing Capacity	907 kg trailer with brakes 674 kg trailer without brakes
Fuel Capacity	20.5 L

FEATURES

Gauge	4.5-in. digital display: Speedometer, tachometer, odometer, trip & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock
Instrumentation	Lighter type DC Outlet in console, standard connector in the back (15-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Winch	3,500-lb (1,588 kg) winch
T-Category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn
Seat	Reinforced seat skin Convertible Rack System (CRS)
Protection	Heavy-Duty front bumper, Central skid plate, Heated grips

2-year BRP limited warranty Factory warranty

©2021 Bombardier Recreational Products Inc. (BRP), All rights reserved. ¹⁰⁴, * and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. *Visco-Lok is a trademark of GKN Viscodrive GmbH. *All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs dont mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

