can-am. **OUTLANDER MAX XU+ 650 T**

HIGHLIGHTS

- Rotax® V-Twin engine
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
 Intelligent Throttle Control (iTC™) with riding modes
- Speed limiter
- 3,500-lb (1,588 kg) winch
- 26 in. (66 cm) Carlisle ACT HD 6-ply tires
- 12 in. (30.5 cm) aluminum wheels
- Arched Double A-arm front suspension with front sway bar
 Torsional Trailing arm Independent (TTI) rear suspension
- Up to 750 kg of towing capacity
- Heavy-duty front bumper
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- RF Digitally Encoded Security System (D.E.S.S.™)
- 650 W magneto
- Multifunction digital gauge
- 5.7 gal (21.4 L) water-resistant rear compartment



n 1	\sim	B 1	-
IN	GI	IN	ES

Туре	44 kW (59 hp), Rotax® 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra low L, standard engine braking
Drive Train	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed Category	Up to 60 km/h

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel
Rear Shocks	Oil

TIRES / WHEELS

Front Tires	Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)	
Rear Tires	Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)	
Wheels	12 in. (30.5 cm) cast-aluminum	

BRAKES

Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	827 lb (375 kg)	
LxWxH	94 x 48 x 53 in. (238.8 x 121.9 x 135 cm)	
Wheelbase	59 in. (149.9 cm)	
Ground Clearance	12 in. (30.5 cm)	
Seat Height	34.5 in. (87.7 cm)	
Rack Capacity	Front: 100 lb (45 kg) / Rear: 200 lb (90 kg)	
Storage Capacity	Rear: 5.7 gal (21.4 L)	
Towing Capacity	750 kg trailer with brakes and 335 kg trailer without brakes	
Fuel Capacity	5.4 gal (20.5 L)	

FEATURES

Gauge	4.5-in. digital display: Speedometer, tachometer, odometer, trip & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock
Instrumentation	Lighter type DC Outlet in console, standard connector in the back (15-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Winch	3,500-lb (1,588 kg) winch
T-Category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn
Seat	Reinforced seat skin
Protection	Heavy-duty front bumper Heated grips Mudguards

WARRANTY

Factory warranty 2-year BRP limited warranty

©2021 Bombardier Recreational Products Inc. (BRP), All rights reserved. ¹⁰⁴, * and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. *Visco-Lok is a trademark of GKN Viscodrive GmbH. *All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs dont mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

