



## шеш енте

| півпівпів            |  |
|----------------------|--|
| TOUGH                | <ul> <li>Heavy-duty Rotax® engine</li> <li>Smooth, durable and responsive transmission</li> <li>True Can-Am DNA with a strong identity</li> </ul>  |
| CAPABLE              | Work or ride with confidence     Meaningful and versatile functionality     Easy handling and capabilities   |
| CLEVER               | Advanced comfort and intuitive cockpit with optimized visibility     Multifunction cargo box with sturdy tailgate and smart storage     1-year maintenance free and easy access to key maintenance components  |
| PLATFORM<br>FEATURES | - 83 in. (211.5 cm) wheelbase - 13 in. (33 cm) of ground clearance - Dynamic Power Steering (DPS™) - ECO™ / ECO™ off / Work modes - 2,500 lb (1136 kg) towing capacity - Multifunction cargo box - 27 in. (68.6 cm) Maxxis Bighorn 2.0† tires - Rear differential with Turf mode - 4.5 in. (11.4 cm) digital display |

## SPECIFIC TO TRAXTER XT **HD10 PACKAGE**

- 64 in. (162.5 cm) wide with Arched A-arm
- Visco-Lok† QE auto-locking front differential 14 in. (35.6 cm) cast-aluminum wheels
- VERSA-PRO bolster bench seat with reinforced XT seat skin and adjustable driver seat
- HMWPE full skid plate
- 4,500-lb (2,041 kg) winch with roller fairlead
- XT front bumper
- · Full hard roof
- · Brake holding mechanism
- · Left and right sides mirrors

## **ENGINE**

| Litaiit              |  |  |  |
|----------------------|--|--|--|
| Туре                 | 61 kW (82 hp) / 69 lb-ft, Rotax® 976 cc, V-twin,<br>liquid cooled  |  |  |
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel<br>Injection (EFI)  |  |  |
| Transmission         | PRO-TORQ CVT Transmission with Quick Response<br>System (QRS), high airflow ventilation and Electronic<br>Drive Belt Protection<br>Extra-L / H / N / R / P |  |  |
| Drive Train          | Selectable Turf Mode / 2WD / 4WD<br>with Visco-Lok† QE auto-locking front differential   |  |  |
| Driving Assistance   | Electronic Hill Descent Control<br>ECO™ / ECO™ Off / Work modes<br>Brake Holding Mechanism   |  |  |
| Power Steering       | Dynamic Power Steering (DPS™)  |  |  |
| SUSPENSIONS          |  |  |  |
| Front Suspension     | Arched double A-arm / 11 in. (27.9 cm) travel  |  |  |
| Front Shocks         | Twin tube gas charged shocks   |  |  |
| Rear Suspension      | Arched TTA with external sway bar /<br>11 in. (27.9 cm) travel   |  |  |
| Rear Shocks          | Twin tube gas charged shocks   |  |  |
| TIRES / WHEELS       |  |  |  |
| Front Tires          | Maxxis Bighorn 2.0† 27 x 9 x 14 in.<br>(68.6 x 22.9 x 35.6 cm)   |  |  |
| Rear Tires           | Maxxis Bighorn 2.0† 27 x 11 x 14 in.<br>(68.6 x 27.9 x 35.6 cm)  |  |  |
| Wheels               | 14 in. (35.6 cm) cast-aluminum   |  |  |
| BRAKES               |  |  |  |
| Front                | Dual 220 mm disc brakes with<br>hydraulic twin-piston calipers   |  |  |
| Rear                 | Dual 220 mm disc brakes with   |  |  |
|                      |  |  |  |



| DIMENSIONS | / CA | ries |
|------------|------|------|

| Cage                               | Profiled cage.<br>ROPS approved<br>1,600.6 lb (726 kg)   |  |
|------------------------------------|--|--|
| Estimated Dry Weight *             |  |  |
| LxWxH                              | 125.7 x 64 x 80 in. (319.4 x 162.5 x 203.2 cm)   |  |
| Wheelbase                          | 83 in. (211.5 cm)  |  |
| Ground Clearance                   | 13 in. (33 cm)   |  |
| Cargo Box Dimensions               | go Box Dimensions 38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)  |  |
| Cargo Box Capacity                 | 1,000 lb (454 kg)  |  |
| Power tilt bed N/A                 |  |  |
| Tailgate Load Capacity             | 250 lb (113.4 kg)  |  |
| Storage Capacity                   | Total: 16.2 gal (61.3 L) Under dash: 6 gal (22.8 L) Waterproof and removable box under passenger seat 5.6 gal (21 L) Dash: 2 gal (7.7 L) Water-resistant and removable toolbox: 1.7 gal (6.3 L |  |
|                                    | Armrests and cup holders: 0.9 gal (3.5 L)  |  |
| Towing Capacity                    | 2,500 lb (1136 kg)   |  |
| Payload Capacity 1,500 lb (680 kg) |  |  |
| Fuel Capacity 10.6 gal (40 L)      |  |  |
| Person Capacity                    | 3  |  |

| Person Capacity | 3   |  |
|-----------------|---|--|
| FEATURES        |   |  |
| Gauge           | 4.5 in. (11.4 cm) wide digital display: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, ECO™ / ECO™ Off / Work modes, seat belt and 4 x 4 indicator, front and rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature |  |
| Battery         | 12-V (30 amp/h)   |  |
| Magneto         | 650-W   |  |
| Instrumentation | Lighter type DC outlets in the console (10-A) and two lighted USB port in the dash storage (10-A)   |  |
| Lighting        | 140 W lighting output from four 35-W reflectors<br>ensuring a wide visiblity and LED tail lights  |  |
| Winch           | 4,500-lb (2,041 kg) winch with roller fairlead  |  |
| Seat            | VERSA-PRO bolster bench seat for additional lateral<br>support with passenger seats flipping up, adjustable<br>driver seat, underside hooks, reinforced XT seat skin and<br>contoured bench to improve entrance/exit of the cab   |  |
| Steering Wheel  | Adjustable tilt steering  |  |
| Protection      | XT front bumper<br>HMWPE full skid plate<br>Full hard roof  |  |
| Hitch Type      | 2-in hitch receiver   |  |
| WARRANTY        |   |  |

©2021 Bombardier Recreational Products Inc. (BRP). All rights reserved. M, and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. Base model dry weight shown. Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Ride responsibly. BRP high recommends that all ATV drivers take a training ocourse. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs dont mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

Factory warranty

hydraulic single-piston calipers



2-year BRP limited warranty