MY23 MAVERICK X RS TURBO RR WITH SMART-SHOX



Intense Blue, Carbon Black & Chalk Gray

HIGHLIGHTS

- Smart-Lok™* front differential
- Smart-Shox** Technology featuring DDA Valve
- FOX† 3.0 PODIUM† shocks with bypass
- · Belt monitoring system
- 850 W Magneto
- 7.6 in. (19.3 cm) digital display with keypad
- X-package graphics/seats
- 4-point harness with shoulder pads
- · Can-Am LED signature
- 14 in. (35.6 cm) cast-aluminum beadlock wheels
- 32 in. (81.3 cm) Maxxis Carnivore† tires
- Full roof
- HMWPE full skid plate
- · Horn, Buzzer & Evap system

ENGINE

Triple Black

ENGINE	
Туре	149 kW (200 hp*), Rotax® ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok * technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Double A-arm with sway bar / 22 in. (55.9 cm) travel / Trophy truck inspired arms
Front Shocks	FOX† 2.5 PODIUM† Piggyback with bypass and Smart-Shox** Technology featuring DDA Valve (Dynamic Damping Adjustment)
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar / 24 in. (61 cm) travel
Rear Shocks	FOX† 3.0 PODIUM† remote reservoir with bypass and Smart-Shox** Technology featuring DDA Valve (Dynamic Damping Adjustment) **Smart-Shox was developed in conjunction with Tractive Industries, a market leader in the suspension industry

TIRES / WHEELS

Front Tires / Rear Tires	Maxxis Carnivore† 32 x 10 / 10 x 14 in. (81.3 x 25.4 / 25.4 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum beadlock

BRAKES

Rear Dual 248 mm disc brakes with hydraulic twin-pistor	n calipers

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	1,699 lb (770.7 kg)	
Chassis / Cage	Dual-phase 980 steel	
LxWxH	132 x 72.7 x 68.5 in. (335.3 x 184.7 x 174 cm)	
Wheelbase	102 in. (259.1 cm)	
Ground Clearance	16 in. (40.6 cm)	
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach	
Storage Capacity	Total: 2.5 gal (9.4 L)	
Fuel Capacity	10.5 gal (40 L)	

FEATURES

7.6 in. (19.3 cm) wide digital display with keypad
DC Outlet (10-A)
850 W
RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
LED headlights LED signature LED tail lights
N/A
Integrated front bumper Quarter-doors Full roof 4-point harness with shoulder pads HMWPE full skid plate Rear tow hook

WARRANTY

WARRANTI		
Factory warranty	2-year BRP limited warranty	

^{*149}kw/200hp based on MY22 U.S. EPA certification, or 145kw/195hp based on current EU NRMM certification.



