

2020

GRAND TOURING SPORT NEW

PACKAGE HIGHLIGHTS

- Rotax® 600 ACE™ engine with 650W magneto
- RAS™ 3 front suspension
- REV® Gen4 platform with wide-design bodywork
- SilentDrive™ system with 381 x 3487 x 32 mm (15 x 137 x 1.25 in.) Silent Track II
- 26.5-in. Ultra-high windshield with side deflectors
- 2-up seat with heated passenger handholds and air deflectors
- Mechanical reverse
- Reversible throttle lever (thumb or finger activated)
- Pivoting mirrors
- Heated driver's visor power outlet
- SC™-5M rear suspension
- Pilot™ DS 2 skis
- Brembo brake with braided stainless-steel brake line
- 4.5-in. digital display
- iTC™ Engine mapping modes (Standard, Sport or ECO®)
- Air radiator with electric fan



GRAND TOURING SPORT 600 ACE™ shown

ROTAX® ENGINE

600 ACE™

Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7,250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	36 L
Oil tank capacity	2.1 L

POWERTRAIN

Drive clutch type	eDrive™ 2
Driven clutch type	QRS
Engagement	2,200 RPM
Small sprocket number of teeth	21
Large sprocket number of teeth	51
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm
Brake system	Brembo brake with stainless-steel braided brake line

FEATURES

Frame	REV® Gen4
Bodywork	Wide design
Skis	Pilot™ DS 2
Seating	2-up
Handlebar	U-shaped aluminum

Riser block height	120 mm
Starter	Electric
Reverse	Mechanical
Heated throttle lever/ grips	Standard (driver and passenger)
Gauge	4.5-in. digital display

Mirrors	Standard
Windshield	673 mm
Runner	Round 1/2
Carbide configuration	102 mm at 90°
Hitch	Optional

COLOR

Catalyst Grey / Black

DIMENSIONS

Vehicle overall length	3,038 mm
Vehicle overall width	1,217 mm
Vehicle overall height	1,405 mm
Ski stance	1,077 mm
Ski overall length	1,066 mm
Track nominal width	381 mm
Track nominal length	3,487 mm
Track profile height	31.8 mm Silent Track II

SUSPENSION

Front suspension	RAS™ 3
Front shock	Motion Control
Front suspension max. travel	220 mm
Rear suspension	SC™-5M
Center shock	Motion Control
Rear shock	HPG™
Rear suspension max. travel	245 mm



GRAND TOURING SPORT 600 ACE™ shown

FEATURE HIGHLIGHTS



iTC™ with ECO® mode

Intelligent Throttle Control (iTC™) throttle-by-wire technology includes three shift-on-the-fly driving modes (Sport, Standard, ECO®).




Finger throttle position

Throttle block can be rotated to be used as either a traditional thumb throttle or unique finger throttle.



Ultra-high windshield

Sculpted to offer improved rider and passenger wind deflection.



2-up seat with passenger handholds

Comfortable 2-up seat with backrest, including handholds.



4.5-in. digital display

All-digital LCD gauge cluster with flatter viewing angle for an easy-to-read info center whether standing or sitting.

GAUGE FEATURES

Speedometer	Standard
Tachometer	Standard
Fuel	Standard
Engine temperature	Standard