# 2022 SUMMIT<sup>®</sup> X<sup>®</sup> WITH EXPERT PACKAGE

The ultimate deep-snow sled with features sharpened for technical terrain riding.



# // WHAT'S NEW

• Narrower 34 in. ski stance

**ROTAX® ENGINE** 

# // PACKAGE HIGHLIGHTS

- Two ULTIMATE color options with panel wrap: supreme look and finish, maximum protection
- Rotax® 850 E-TEC® or 850 E-TEC Turbo engines available
- Premium shock package with stiffer calibration
- Short tunnel with lightweight snowflap
- RAS™ 3 front suspension with lightweight ski spindle and revised ski stopper
- tMotion^{\ensuremath{\mathsf{TM}}} rear suspension with ice scratchers and adjustable limiter strap
- E-TEC® SHOT™ starter standard
- Full-length extruded-profile running boards with large openings

850 E-TEC®

- One-piece lightweight hood on all models
- Flexible handguards
- Short riser block (120 mm/4.7 in.)

## COLOR

ULTIMATE Liquid Titanium / Carbon Black

configurations

• DS 3 skis

• 4.5 in. digital display

• Belt monitoring system

SUMMIT® X® WITH EXPERT PACKAGE 165 850 E-TEC® TURBO SHOWN

• Sea-level calibration available on select

• Smaller-diameter handlebar ends and handgrips

• Ultra-compact and lightweight deep-snow seat

ULTIMATE Triple Black

### SUSPENSION

Front suspension	RAS™ 3	
Front shock	HPG™ Plus with lightweight springs	
Front suspension travel	215 mm/8.5 in.	
Rear suspension	tMotion™ with adjustable limiter strap	
Center shock	HPG™ Plus with lightweight spring	
Rear shock	KYB† PRO 36 Easy-Adjust	
Rear suspension travel	239 mm/9.4 in. (154, 165 in.) 242 mm/9.5 in. (175 in.)	

### FEATURES

Frame	REV® Gen4
Bodywork	Narrow design
Skis	Pilot™ DS 3
Seating	Deep-snow ultra-compact and lightweight
Handlebar	Tapered U-shaped aluminum with J-hooks/Low grab handle/Flexible handguards
Riser block height	120 mm/4.7 in.
Starter	SHOT
Reverse	RER™
Brake system	Brembo racing brake with stainless-steel braided brake line
Heated throttle lever/grips	Standard
Gauge type	4.5 in. digital display
Windshield	Optional
Runner – Carbide	Square 3/8 – 4 in.
Bumpers (front/rear)	Std/Std

Engine details	Liquid-cooled, two-stroke, turbocharged, eRAVE™	Liquid-cooled, two-stroke, eRAVE™
Horsepower	165 up to 8,000 ft.	165
Cylinders – Displacement	2 – 849 cc	2 – 849 cc
Bore – Stroke	82 mm – 80.4 mm	82 mm – 80.4 mm
Carburation	E-TEC <sup>®</sup> direct injection with additional booster injectors	E-TEC® direct injection with additional booster injectors
Fuel type – Octane	Premium unleaded – 91	Premium unleaded – 91
Fuel tank	36 L/9.5 US gal	36 L/9.5 US gal
Oil tank capacity	3.4 L/3.6 qt	3.4 L/3.6 qt
POWERTRAIN		
Drive clutch	pDrivo™ with aliakara	nDrivo™ with aliakara

850 E-TEC<sup>®</sup> TURBO

DRY WEIGHT				
Drive sprocket pitch	89 mm/3.5 in.	89 mm/3.5 in.		
Driven clutch	QRS Vent Plus	QRS Vent Plus		
Drive clutch	pullive with clickers	punve with clickers		

D	R	Y	W	EI	G	Η

Dry weight	208 kg/458 lb (154 in.) 212 kg/468 lb (165 in.)	198 kg/437 lb (154 in.) 202 kg/446 lb (165 in.)
	215 kg/474 lb (175 in.)	

### DIMENSIONS

Overall vehicle length	3,188 mm/125.5 in. (154 in.) 3,299 mm/129.9 in. (165 in.) 3,454 mm/136 in. (175 in.)	
Overall vehicle width	1,080 to 1,110 mm/42.5 to 43.7 in.	
Overall vehicle height	1,306 mm/51.4 in.	
Ski stance	864 mm/34 in.	
Track (Length x Width x Profile)	PowderMax <sup>1</sup> Light 154 x 16 x 2.5 in. 154 x 16 x 3.0 in. 165 x 16 x 3.0 in. 175 x 16 x 3.0 in. 850 E-TEC Turbo only	


# 2022 SUMMIT<sup>®</sup> X<sup>®</sup> WITH EXPERT PACKAGE

# // FEATURE HIGHLIGHTS



### 1 Rotax 850 E-TEC<sup>®</sup> Turbo engine

The first-ever factory-built 2-stroke turbocharged engine in any industry. It boasts instant response and a full 165 HP up to 8,000 ft of elevation. Sophisticated design integrates flawlessly with the REV Gen4 platform for maximum agility. Factory installation ensures peace of mind.



#### 2 Specialized ergonomics

Input from our team of backcountry experts resulted in a purpose-built sled for a better deep-snow experience with lower seat height, shorter riser, smaller-diameter handlebars and low handlebar strap for the ultimate advantage in the most technical terrains.



#### 3 tMotion<sup>™</sup> with adjustable limiter strap

Quickly and easily change the limiter strap length for the desired ski lift without crawling under the sled.





#### 4 Narrower 34 in. ski stance

Makes it easier to initiate rollup, lowers the center of gravity requiring less effort to balance the sled and provides a larger window for the ideal balance point. Also improves traction at the balance point.

#### (See website for image)

### 5 Lightweight features

Weight savings from the one-piece lightweight hood, ski spindle, stopper, springs, seat and more make technical maneuvers easier than ever.



#### 6 E-TEC® SHOT™ starter

Push-button starting with almost no added weight. Uses energy stored in the lightweight ultracapacitor to turn the magneto and with E-TEC® technology, starts the engine.





©2021 Bombardier Recreational Products Inc., (BRP). All rights reserved. TM, (a) and the BRP logo are trademarks of BRP or its affiliates. Products are distributed in the USA by BRP US Inc. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Printed in Canada.