MY23 RENEGADE 650 T



liquid cooled

Braking (iEB™)

Control (BTC)

More than 60 km/h

9.2 in. (23.3 cm) travel

9.9 in. (25.1 cm) travel

(63.5 x 27.9 x 30.5 cm)

twin-piston calipers

twin-piston caliper

Gas

Gas

44 kW (59 hp), Rotax® 650 cc V-twin,

Intelligent Throttle Control (iTC[™]) with

CVT, P / R / N / H / L, Intelligent Engine

Selectable 2WD / 4WD with Brake Traction

Tri-Mode Dynamic Power Steering (DPS)

Arched double A-arm with front sway bar

Torsional Trailing arm Independent (TTI)

ITP Holeshot† ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)

ITP Holeshot† ATR 25 x 11 x 12 in.

Dual 214 mm disc brakes with hydraulic

Single 214 mm disc brake with hydraulic

12 in. (30.5 cm) cast-aluminum

Electronic Fuel Injection (EFI)

ENGINE

Fuel Delivery System

Transmission

Drive Train

Power Steering

Speed Category

SUSPENSIONS

Front Shocks

Rear Shocks

Rear Tires

Wheels

BRAKES

Front

Rear

Front Suspension

Rear Suspension

TIRES / WHEELS Front Tires

Туре

HIGHLIGHTS

Tri-Mode Dynamic Power Steering (DPS)

 Anti-Lock Braking System (ABS) · Gas shocks

12 in. (30.5 cm) cast-aluminum wheels

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	750 lb (340 kg)
LxWxH	86 x 48 x 49 in. (218.4 x 121.9 x 124 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	10.5 in. (26.7 cm)
Seat Height	34.5 in. (87.7 cm)
Rack Capacity	Rear: 35 lb (16 kg)
Storage Capacity	N/A
Towing Capacity	660 kg trailer with brakes and 335 kg trailer without brakes
Fuel Capacity	5.4 gal (20.5 L)
EEATURES	
FEATURES	
Gauge	4.5 in. digital display
Gauge	4.5 in. digital display DC Outlet, 15-A connector
Gauge	5 1 7
Gauge Instrumentation Ingnition	DC Outlet, 15-A connector RF Digitally Encoded Security System
Gauge Instrumentation Ingnition Lighting	DC Outlet, 15-A connector RF Digitally Encoded Security System (D.E.S.S.™)
Gauge Instrumentation Ingnition Lighting Winch	DC Outlet, 15-A connector RF Digitally Encoded Security System (D.E.S.S [™]) LED headlights N/A
FEATURES Gauge Instrumentation Ingnition Lighting Winch T-Category features Seat	DC Outlet, 15-A connector RF Digitally Encoded Security System (D.E.S.S [™]) LED headlights N/A Towing hitch with trailer plug, directional
Gauge Instrumentation Ingnition Lighting Winch T-Category features	DC Outlet, 15-A connector RF Digitally Encoded Security System (D.E.S.S.™) LED headlights N/A Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn

Front bumper

WARRANTY

Protection

Factory warranty

2-year BRP limited warranty

©2022 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, * and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †All trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by the age of 16 and older. Never carry passengers on any ATV not specifically designated for such use. Some models depicted may include optional equipment.

