

# MY23 MAVERICK TRAIL 700 T



Catalyst Gray

## ENGINE

|                      |   |
|----------------------|---|
| Type                 | 39 kW (52 hp) / 41 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc single cylinder, liquid cooled, with catalytic converter |
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)  |
| Transmission         | PDrive primary CVT with engine braking and Electronic Drive Belt Protection<br>L / H / N / R / P                                      |
| Drive Train          | Selectable 2WD / 4WD with Visco-Lok† auto-locking front differential  |
| Driving Assistance   | Electronic Hill Descent Control<br>SPORT / ECO™ modes   |
| Power Steering       | N/A   |

## SUSPENSIONS

|                  |  |
|------------------|--|
| Front Suspension | Double A-arm with sway bar / 10 in. (25.4 cm) travel |
| Front Shocks     | Twin tube gas charged shocks                         |
| Rear Suspension  | TTA with sway bar / 10.5 in. (26.7 cm) travel        |
| Rear Shocks      | Twin tube gas charged shocks                         |

## TIRES / WHEELS

|                    |   |
|--------------------|---|
| Front & Rear Tires | Carlisle ACT 26 x 8 / 9 x 12 in. (66 x 20.3 / 22.9 x 30.5 cm) |
| Wheels             | 12 in. (30.5 cm) steel  |

## BRAKES

|                     |   |
|---------------------|---|
| Front & Rear Brakes | Dual 220 mm disc brakes with hydraulic twin-piston calipers |
|---------------------|---|

## DIMENSIONS / CAPACITIES

|                        |   |
|------------------------|---|
| Estimated Dry Weight * | 1,256 lb (569.7 kg)                               |
| Chassis / Cage         | Profiled cage<br>ROPS approved                    |
| L x W x H              | 118 x 62.8 x 69 in.<br>(300.5 x 159.6 x 175.3 cm) |
| Wheelbase              | 90.6 in. (230.1 cm)                               |
| Ground Clearance       | 10 in. (25.4 cm)                                  |
| Cargo Box Capacity     | 300 lb (136 kg)                                   |
| Towing Capacity        | 1,500 lb (682 kg)                                 |
| Storage Capacity       | Total: 5.3 gal (20.2 L)                           |
| Fuel Capacity          | 10 gal (38 L)                                     |

## FEATURES

|                 |  |
|-----------------|--|
| Gauge           | 7.6 in. (19.3 cm) wide digital display with keypad   |
| Instrumentation | DC outlet (10-A)   |
| Ignition        | RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button  |
| Magneto         | 650-W  |
| Lighting        | Front lighting output 110 W<br>LED tail lights with halo glow effect   |
| Winch           | N/A  |
| Steering Wheel  | Adjustable tilt steering   |
| Protection      | Integrated front steel bumper, Full skid plate<br>Mudguards and Mudflaps   |
| Hitch Type      | 2 in. hitch receiver with rear hitch and tow ball  |
| T-Cat Features  | Horn, flashers and position lamps, side mirrors,<br>license plate support, hook on front metal bumper, driver seat detector, low brake fluid sensor, 7-pin trailer connexion (12V) |

## WARRANTY

|                  |                             |
|------------------|-----------------------------|
| Factory warranty | 2-year BRP limited warranty |
|------------------|-----------------------------|



©2022 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. \*Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

A BRP BRAND

