

# MY25 MAVERICK SPORT MAX DPS 1000R T ABS



Triple Black

ENGINES	1000R
Type	95 hp, Rotax® 976 cc, V-twin, liquid cooled, catalytic converter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with open front differential with ABS system
Driving Assistance	Electronic Hill Descent Control SPORT / ECO™ modes
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm with sway bar / 11.5 in. (29.2 cm) suspension travel
Front Shocks	SHOWA 2.0
Rear Suspension	TTA with sway bar / 12 in. (30.5 cm) suspension travel
Rear Shocks	SHOWA 2.0

TIRES / WHEELS	
Front / Rear Tires	Maxxis Liberty† 28 x 10 x 14 in.
Wheels	14 in. cast-aluminum

BRAKES	
Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers

## PACKAGE HIGHLIGHTS

- Visco-Lok† QE front differential
- Dynamic Power Steering (DPS™)
- Ergoprint seats with color accents
- Maxxis Liberty† 28 x 10 x 14 in.
- 14 in. cast-aluminum
- RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
- Horn with turning signal lever
- Flashers and position lamps (CE)
- Left and right sides mirrors
- Hook on front metal bumper
- Driver seat detector
- Dynamic Brake Control (ABS + HHC + HDC)
- Dynamic Traction Control (BTC + DTC)
- Dynamic Traction Control (TCS "désactivable")
- Speed limiter: 40 - 60 - 105 (Km/h)
- Sensor on brake main cylinder
- Specific exhaust

DIMENSIONS / CAPACITIES	
Cage	Profiled cage. ROPS approved
Estimated Dry Weight*	1,697 lb (769.7 kg)
L x W x H	149 x 62.1 x 81.2 in. (378.4 x 157.8 x 206.2 cm)
Wheelbase	120.6 in. (306.3 cm)
Ground Clearance	12 in. (30.5 cm)
Cargo Box Capacity	300 lb (136 kg)
Storage Capacity	Total: 6.5 gal (24.7 L)
Towing Capacity	1,500 lb (680 kg)
Fuel Capacity	10 gal (38 L)
Person Capacity	4

FEATURES	
Gauge	7.6 in. wide digital display with keypad
Magneto	650-W
Instrumentation	DC outlet (10-A)
Lighting	Front lighting output 110-W LED tail lights
Winch	N/A
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper T-Net (driver), Regular Net (passenger front) and half doors (rear only) Full skid plate Mudguards
Hitch Type	2 in. hitch receiver with rear hitch, tow ball and trailer connexion

WARRANTY & EXTENDED SERVICE	
Factory warranty	2-year BRP limited warranty



REQUEST A QUOTE



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. \*Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrives GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.