

MY25 MAVERICK TRAIL DPS 700 T ABS



Triple Black

ENGINES		700
Type	52 hp / 42 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc single cylinder, liquid cooled, catalytic converter	
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	pDrive primary CVT with engine braking and Electronic Drive Belt Protection L / H / N / R / P	
Drive Train	Selectable Turf Mode / 2WD / 4WD with open front differential with ABS system	
Driving Assistance	Electronic Hill Descent Control SPORT / ECO™ modes	
Power Steering	Dynamic Power Steering (DPS)	
SUSPENSIONS		
Front Suspension	Double A-arm with sway bar / 10 in. (25.4 cm) suspension travel	
Front Shocks	Twin tube gas charged shocks	
Rear Suspension	TTA with sway bar / 10.5 in. (26.7 cm) suspension travel	
Rear Shocks	Twin tube gas charged shocks	
TIRES / WHEELS		
Front / Rear Tires	Carlisle ACT 26 x 8/9 x 12 in.	
Wheels	12 in. cast-aluminum	
BRAKES		
Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers	
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers	

PACKAGE HIGHLIGHTS

- Visco-Lok† QE front differential
- Dynamic Power Steering (DPS™)
- Ergoprint seats with color accents
- RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
- New evap system
- Horn with turning signal lever
- Flashers and position lamps (CE)
- Left and right sides mirrors
- Hook on front metal bumper
- Driver seat detector
- Dynamic Brake Control (ABS + HHC + HDC)
- Dynamic Traction Control (BTC + DTC)
- Sensor on brake main cylinder
- Specific exhaust

DIMENSIONS / CAPACITIES

Cage	Profiled cage ROPS approved
Estimated Dry Weight*	1,271 lb (576.5 kg)
L x W x H	118 x 62.8 x 69 in. (300.5 x 159.6 x 175.3 cm)
Wheelbase	90.6 in. (230.1 cm)
Ground Clearance	10 in. (25.4 cm)
Cargo Box Capacity	300 lb (136 kg)
Storage Capacity	Total: 5.3 gal (20.2 L)
Towing Capacity	1,500 lb (680 kg)
Fuel Capacity	10 gal (38 L)
Person Capacity	2

FEATURES

Gauge	7.6 in. wide digital display with keypad
Magneto	650-W
Instrumentation	DC outlet (10-A)
Lighting	Front lighting output 110-W LED tail lights
Winch	N/A
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper Full skid plate Mudguards T-Net (driver), Regular Net (passager front)
Hitch Type	2 in. hitch receiver with rear hitch, tow ball and trailer connexion

WARRANTY & EXTENDED SERVICE

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------



REQUEST A QUOTE



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.