MY25 OUTLANDER MAX XT 700 T ABS



Platinum Satin

PACKAGE HIGHLIGHTS

- · Tri-Mode Dynamic Power Steering (DPS)
- · Intelligent Engine Braking (iEB™)
- · Selectable 2WD / 4WD with BTC (Brake traction Control)
- \cdot 26 in. XPS Trail Force with 14 in. Aluminum wheels
- · 3,500 lb (1,588 kg) winch
- \cdot Front bumper, rear bumper, full skid plate
- · Premium glovebox with cellphone holder and USB charger
- $\cdot \ \mathsf{Front} \ \mathsf{dropdown} \ \mathsf{storage}$
- · Tow ball
- · Horn, flashers and mirrors

ENGINES	700
Туре	50 hp / 41 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary CVT L / H / N / R / P
Drive Train	Selectable 2WD / 4WD with BTC (Brake traction Control)
Driving assistance	Work / Standard / Sport modes Intelligent Engine Braking (iEB™)
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Double A-arm 9.75 in. (24.8 cm) travel
Front Shocks	Twin tube
Rear Suspension	Double A-arm 10.25 in. (26 cm) travel
Rear Shocks	Twin tube
TIRES / WHEELS	
Front & Rear Tires	XPS Trail Force 26 x 8/10 x 14 in.
Wheels	14 in. Aluminum
BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

Estimated Dry Weight *	910.6 lb (413.1 kg)
L x W x H (includes mirrors)	94.2 x 47.6 x 57.4 in. (239.2 x 120.9 x 145.6 cm)
Wheelbase	60.4 in. (153.5 cm)
Ground Clearance	12.5 in. (31.8 cm)
Seat Height	38.6 in. (98 cm)
Rack Capacity	Front: 120 lb (54.4 kg) / Rear: 240 lb (109 kg)
Storage Capacity	9 gal (34 L)
Towing Capacity	1,830 lb (830 kg) trailer with brakes / 870 lb (394 kg) trailer without brakes
Fuel Capacity	5.1 gal (19.5 L)
Gauge	4.5 in. Digital Display
dauge	4.5 III. Digital Display
Instrumentation	LISB Phone charger
	USB Phone charger
	RF Digitally Encoded Security System (D.E.S.S.™)
Ingnition	
Ingnition Lighting	RF Digitally Encoded Security System (D.E.S.S.™) LED headlights and tail lights
Ingnition Lighting Winch	RF Digitally Encoded Security System (D.E.S.S.™) LED headlights and tail lights LED signature
Instrumentation Ingnition Lighting Winch Seat Handlebar	RF Digitally Encoded Security System (D.E.S.S.™) LED headlights and tail lights LED signature 3,500 lb (1,588 kg) winch
Ingnition Lighting Winch Seat	RF Digitally Encoded Security System (D.E.S.S.™) LED headlights and tail lights LED signature 3,500 lb (1,588 kg) winch Standard
Ingnition Lighting Winch Seat Handlebar	RF Digitally Encoded Security System (D.E.S.S.™) LED headlights and tail lights LED signature 3,500 lb (1,588 kg) winch Standard Standard
Ingnition Lighting Winch Seat Handlebar	RF Digitally Encoded Security System (D.E.S.S.™) LED headlights and tail lights LED signature 3,500 lb (1,588 kg) winch Standard Standard Front bumper, rear bumper, full skid plate
Ingnition Lighting Winch Seat Handlebar Protection	RF Digitally Encoded Security System (D.E.S.S.™) LED headlights and tail lights LED signature 3,500 lb (1,588 kg) winch Standard Standard Front bumper, rear bumper, full skid plate





