MY25 RENEGADE X MR 1000R



PACKAGE HIGHLIGHTS

- · Tri-Mode Dynamic Power Steering (DPS)
- · Intelligent Engine Braking (iEB™)
- · Visco-4Lok auto-locking front differential
- · Rotax® snorkeled V-Twin engine with relocated CVT intake and outlet
- \cdot 30 in. ITP Cryptid tires with 14 in. aluminum beadlock wheels
- · 3,500-lb (1,588 kg) winch
- · Front & central aluminum skid plate
- · Heavy-duty Front bumper, rear bumper
- \cdot Aluminum taper-profile handlebar with grab handle and full-wrap handguards
- V pookogo

Factory warranty

ENGINES	1000R
Туре	91 hp, Rotax 976 cc V-twin, snorkeled, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT Extra low L / H / N / R / P
Drive Train	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok front differential
Driving assistance	Work / Standard / Sport modes Intelligent Engine Braking (iEB™)
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar
Front Shocks	FOX† 1.5 PODIUM† QS3
Rear Suspension	Torsional Trailing arm Independent (TTI)
Rear Shocks	FOX† 1.5 PODIUM† QS3
TIRES / WHEELS	
Front & Rear Tires	ITP Cryptid 30 x 9/9 x 14 in.
Wheels	14 in. cast-aluminum beadlock
BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

Estimated Dry Weight *	971 lb (440 kg)
L x W x H (includes mirrors)	83 x 50 x 56 in. (224 x 127 x 131 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	12.5 in. (31.8 cm)
Seat Height	36.8 in. (93.3 cm)
Rack Capacity	Rear: 35 lb (16 kg)
Storage Capacity	N/A
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)
FEATURES	
Gauge	4.5 in. digital display
Gauge Instrumentation	4.5 in. digital display DC outlet, 15-A connector
Instrumentation	DC outlet, 15-A connector RF Digitally Encoded Security System (D.E.S.S.™)
Instrumentation Ingnition	DC outlet, 15-A connector RF Digitally Encoded Security System (D.E.S.S.™) with cord
Instrumentation Ingnition Lighting	DC outlet, 15-A connector RF Digitally Encoded Security System (D.E.S.S.™) with cord LED headlights
Instrumentation Ingnition Lighting Winch	DC outlet, 15-A connector RF Digitally Encoded Security System (D.E.S.S.™) with cord LED headlights 3,500-lb (1,588 kg) winch

6-month BRP Limited warranty





