


2026 MAVERICK MAX X RS TURBO RR SAS



 Dusty Navy

PACKAGE HIGHLIGHTS

- Smart-Lok™ front differential
- Smart-Shox Technology featuring DDA Valve
- FOX† 3.0 PODIUM† shocks with bypass
- Belt monitoring system
- 850-W Magneto
- 4.5 in. wide digital display with keypad & 10.25 in. touchscreen display
- X-package graphics/seats
- 4-point harness with shoulder pads
- Can-Am LED signature
- 15 in. aluminum beadlock wheels
- 32 in. XPS Trac Force tires
- Full hard roof
- Full heavy-duty HMW plastic skid plate
- RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
- Horn with carling

ENGINES	Turbo RR
Type	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTCTM) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok* True 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)

SUSPENSIONS	
Front Suspension	Double A-arm with sway bar / 22 in. (55.9 cm) suspension travel / Trophy truck inspired arms
Front Shocks	FOX† 2.5 PODIUM† Piggyback with bypass and Smart-Shox Technology featuring DDA Valve (Dynamic Damping Adjustment)
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar / 22 in. (55.9 cm) suspension travel
Rear Shocks	FOX† 3.0 PODIUM† with bypass and Smart-Shox Technology featuring DDA Valve (Dynamic Damping Adjustment)

TIRES / WHEELS	
Front / Rear Tires	XPS Trac Force 32 x 10 x 15 in.
Wheels	15 in. cast-aluminum beadlock

BRAKES	
Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS / CAPACITIES	
Cage	Dual-phase 980 steel
Estimated Dry Weight*	1,942 lb (880.9 kg)
L x W x H	165 x 72.7 x 68.5 in. (419.1 x 184.7 x 174 cm)
Wheelbase	135 in. (342.9 cm)
Ground Clearance	16 in. (40.6 cm)
Cargo Box Capacity	150 lb (68 kg) with LinQ™ quick-attach
Storage Capacity	Total: 3 gal (11.4 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES	
Gauge	4.5 in. wide digital display with keypad & 10.25 in. touchscreen display
Magneto	850-W
Instrumentation	DC outlet (10-A)
Lighting	LED Headlight LED Signature LED tail lights
Winch	N/A
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Protection	Integrated front bumper Quarter-doors Full hard roof 4-point harness with shoulder pads Full heavy-duty HMW plastic skid plate Rear tow hook

WARRANTY & EXTENDED SERVICE	
Factory warranty	2-year BRP limited warranty



REQUEST A QUOTE



©2025 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrives GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.