# 2022



# **HIGHLIGHTS**

- Rotax® V-Twin engine options
- Arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- 3,500 lb (1,588 kg) winch
- · Heavy-duty front and rear bumpers
- 14 in. cast-aluminum wheels
- 26 in. ITP Terracross radial tires
- · Painted plastics for premium look
- · Handlebar wind deflectors
- Convertible Rack System (CRS) with LinQ<sup>™</sup> system
- 5.7 gal (21.4 L) water-resistant rear compartment
- 650 W magneto
- Dynamic passenger comfort ergonomics
- · Multiposition passenger hand grips
- · Raised floorboards



Transmission CVT, P/R/N/H/L, standard engine braking  Drive Train Selectable 2WD/4WD with Visco-Lok† QE auto-locking front differential	ENGINES	650	850	1000R
Injection (EFI) with Electronic Fuel Injection (EFI)  Transmission CVT, P/R/N/H/L, standard engine braking  Drive Train Selectable 2WD/4WD with Visco-Lok† QE auto-locking front differential	Туре	Rotax 650 cc V-twin,	Rotax 854 cc V-twin,	Rotax 976 cc V-twin,
Drive Train  Selectable 2WD/4WD  with Visco-Lok† QE auto-locking front differential	Fuel Delivery System	, ,		
with Visco-Lok† QE auto-locking front differential	Transmission	CVT, P/R/N	CVT, P/R/N/H/L, standard engine braking	
7.14.1.5	Drive Train			
Power Steering   Iri-Mode Dynamic Power Steering (DPS)	Power Steering	Tri-Mode Dynamic Power Steering (DPS)		

Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Oil
Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel
Oil

## **TIRES & WHEELS**

Front Tires ITP Terracross 26 x 8 x 14 in.	
Rear Tires	ITP Terracross 26 x 10 x 14 in.
Wheels	14 in. cast-aluminum

#### BRAKES

Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

CAPACITIES	650	850	1000R
Estimated Dry Weight*	827 lb (375 kg)	874 lb (396 kg)	900 lb (408 kg)
LxWxH	94 x 48 x 5	53 in. (238.8 x 121.9	x 135 cm)
Wheelbase	59 in. (149.9 cm)		
Ground Clearance	11 in. (27.9 cm)		
Seat Height	34.5 in. (87.7 cm)		
Rack Capacity	Front: 100 lb (45 kg)/Rear: 200 lb (90 kg)		
Storage Capacity	Rear: 5.7 gal (21.4 L)		
Towing Capacity	1,650 lb (750 kg)		
Fuel Capacity	5.4 gal (20.5 L)		

### **FEATURES**

DIMENSIONS 9.

Gauge	4.5 in. digital display: speedometer, tachometer, odometer, trip and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge and clock	
Instrumentation	Lighter-type DC outlet in console, standard connector in the back (15 A)	
Anti-Theft System	N/A	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	230 W from twin 60 W projectors and dual 55 W reflectors with tail light/brake light	
Winch	3,500 lb (1,588 kg) winch	
Seat	Convertible Rack System (CRS)	
Protection	Heavy-duty front and rear bumpers Handlebar wind deflectors	

# WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 36 months

Mudguards

