

COMMANDER



ROTAX® ENGINE	600R E-TEC	900 ACE	900 ACE Turbo	COLOUR
				Tactical Grey/Black
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C.	Liquid-cooled, four-stroke D.O.H.C., turbo-charged	
Cylinders	2	3	3	
Displacement	599.4 cc	899.0 cc	899.0 cc	
Bore	72,3 mm	74 mm	74 mm	
Stroke	73 mm	69.7 mm	69.7 mm	
Maximum engine speed	8100 RPM	7250 RPM	7750 RPM	
Carburation	Electronic Direct Injection	EFI	EFI	
Recommended fuel type	Unleaded	Unleaded	Unleaded	
Minimum octane	95	95	95	
Fuel tank		42 liters		
Oil tank capacity (2-stroke)	3,4 liters			

DIMENSIONS	
Vehicle overall length*	3240 mm
Vehicle overall width	1200 mm
Vehicle overall height	1500 mm
Ski stance	996 mm
Track nominal width	500 mm
Track nominal length	3923 mm
Track profile height	44 mm PowderMax

POWERTRAIN	
Gearbox	2F/N/R with push-button reverse
Drive clutch type	pDrive with clickers (600R E-TEC) pDrive with slider shoes (900 ACE) pDrive (900 ACE Turbo)
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION	
Front suspension	LFS with bended lower A-Arms
Front shock	HPG 36
Rear suspension	EasyRide with adjustment
Center shock	HPG 36
Rear shock	HPG 36

FEATURES		
Frame	Radien-X	
Skis	Blade DS+	
Seating	Modular, 1-up	
Handlebar	U-type steel with hooks, low grab handle	
Riser block height	145 mm	
Starter	Electric	
Reverse	RER (600R E-TEC) Electromechanical (ACE)	
Heated throttle lever		Standard
Heated grips		Standard
Gauge		Compact digital display
Windshield		Extra high with side deflectors
Hitch		Standard
Visor Plug front / rear		Front
USB power outlet		Front
Air radiator with fan		Yes
LinQ attachment		Multi-LinQ plate

* Vehicle overall length without snowflap.