

NEW FOR 2023

- Recalibrated Rotax 600RS E-TEC engine
- New color

ROTAX® ENGINE	600RS E-TEC 2	
Cylinders		
Displacement	599.4 cc	
Bore	72,3 mm	
Stroke	73 mm	
Maximum engine speed	8400 RPM	
Carburation	Electronic Direct Injection	
Recommended octane	98	
Oil mixture	3 %	
Fuel tank	18 liters	

DIMENSIONS

Vehicle overall length	3170 mm		
Vehicle overall width	1280 mm		
Vehicle overall height	1190 mm		
Ski stance	1092 mm		
Track (W x L x H)	381 x 3487 x 44 mm		

POWERTRAIN

Drive clutch type Racing pDrive			
Driven clutch type	Team TTS-04 5000 RPM		
Clutch engagement rpm			
Secondary gearing	23/51		
Brake system Brembo Racing 4-pis			

SUSPENSION

Front suspension	LFS Racing		
Front shock	KYB 46 HLCR Kashima		
Front suspension travel	255 mm		
Front springs	34 N/mm		
Rear suspension	PPS ² -3500-R		
Shocks (Center/Rear)	KYB 46 HLCR Kashima		
Springs (Center/Rear)	60/70 N/mm		
Rear suspension travel	390 mm		

FEATURES

Frame	Radien-RS	Riser block height	105 mm
Skis	Pilot Racing	Starter	Manual
Seating	RS	Windshield	-

