



Steep ja deep + Mountain / Deep Snow

ROTAX® ENGINE	600R E-TEC	850 E-TEC	850 E-TEC Turbo R
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, turbocharged, 3-D R.A.V.E.™
Cylinders		2	
Displacement	599.4 cc	849 cc	
Bore	72.3 mm	82 mm	
Stroke	73 mm	80.4 mm	
Maximum engine speed	8100 RPM	7900 RPM	
Carburation	Electronic Direct Injection	Electronic Direct Injection with additional booster injectors	
Recommended fuel type	Unleaded		
Minimum octane	95		
Fuel tank	37 liters		
Oil tank capacity (2-stroke)	3.4 liters		

COLOUR	Bright White / Evo Red Black (spring only)	
DIMENSIONS		
Vehicle overall length*	3060 mm (3700) 3190 mm (3900)	
Vehicle overall width	1120 mm	
Vehicle overall height	1280 mm	
Ski stance	921 mm	
Track nominal width	381 mm	
Track nominal length	3705 mm 3923 mm (64mm) 3912 mm (76mm)	
Track profile height	64 mm PowderMax 76 mm PowderMax X-Light (spring only 3900)	

POWERTRAIN

Drive clutch type	1	Drive with clicke	rs
Driven clutch type		QRS	
Brake system	Hydraulic brake with braided steel brake line, adjustable brake lever, aluminium master cylinder		
DRY WEIGHT			
Dry weight	3700: 207 kg	3700: 215 kg 3900: 217 kg	3700: 221 kg 3900: 223 kg

SUSPENSION

Front suspension	LFS
Front shock	KYB PRO 36 EA-3 R Kashima
Rear suspension	PPS²-DS+
Center shock	KYB 46 Plus Kashima
Rear shock	KYB PRO 46 HLCR Kashima

FEATURES

Frame	Radien²
Skis	Blade DS+
Seating	Shredder DS, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	145 mm
Starter	Manual with SHOT Electric (spring only on 3700)

Reverse	RER
Heated throttle lever	Standard
Heated grips	Standard
Gauge	4.5-in. digital display / 10.25-in Color Display (spring only)
USB power outlet	Yes, in front compartment
LinQ attachment	2 pairs



^{*} Vehicle overall length without snowflap.