2023

EXPEDITION° XTREME



// WHAT'S NEW

• Two Rotax® engines available: 850 E-TEC® and 900 ACE™ Turbo R EXPEDITION XTREME 900 ACE TURBO R SHOWN

// PACKAGE HIGHLIGHTS

- KYB† Pro 36 Easy-Adjust rear shock
- HPG™ Plus front shocks
- RAS $^{\text{TM}}$ X crossover front suspension
- SC[†]-5U articulating rear suspension with locking mechanism (no tool required)
- 20 in. wide Multi-LinQ® plate with 125 lb/56.7 kg cargo capacity
- · Air radiator with fan
- Deep-snow running boards with large openings
- pDrive™ clutch with clickers

- Low handlebar strap
- Flexible handguards
- Electric start

COLOR

Bumpers (front/rear)

- Pilot™ DS 3 skis
- Adjustable ski stance

ROTAX ENGINE	850 E-TEC	900 ACE TURBO R
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged
Cylinders - Displacement	2 - 849 cc	3 - 899 cc
Bore - Stroke (mm)	82 - 80.4	73 – 69.7
Carburation	E-TEC direct injection with additional booster injectors	EFI
Fuel type – Octane	Unleaded – 95	Unleaded – 95
Fuel tank (L/US gal)	42/11.1	42/11.1
Oil tank capacity (L/qt)	3.4/3.6	3.3/3.5
POWERTRAIN		
Drive clutch	pDrive with clickers	pDrive
Driven clutch	QRS Vent Plus	QRS Vent
Drive sprocket pitch	73 mm/2.86 in.	73 mm/2.86 in.
DIMENSIONS		
Overall vehicle length	3,293 mm/129.6 in.	
Overall vehicle width	1,140 to 1,180 mm/44.9 to 46.5 in.	
Overall vehicle height	1,280 mm/50.4 in.	
Ski stance	1,000 mm/39 in. adjustable	
Track (Length x Width x Profile)	Cobra WT: 154 x 20 x 1.8 in.	

Black / Spartan Red		
SUSPENSION		
Front suspension	RAS X	
Front shock	HPG Plus	
Front suspension travel	220 mm/8.7 in.	
Rear suspension	SC-5U	
Center shock	HPG Plus	
Rear shock	KYB Pro 36	
Rear suspension travel	239 mm/9.4 in.	
FEATURES		
Platform	REV® Gen4	
Skis	Pilot DS 3	
Seating	1-up modular with rear seat storage	
Handlebar	Standard with J-hooks/Grab handle	
Riser block height	145 mm/5.7 in.	
Starter	Electric	
Reverse	RER™ (850 E-TEC) Electro-mechanic (Turbo R)	
Air radiator	High-efficiency w/ fan (4-stroke) Fan (2-stroke)	
Brake system	Brembo†	
Heated throttle lever/grips	Standard	
Gauge type	Compact Digital Display	
Windshield	360 mm/14 in.	
Runner – Carbide	Square 3/8 in. – 4 in.	





Heavy-duty/Std